ReliZyme[™]

Enzyme carriers



Resindion S.r.l.

A Group Company of 📥 MITSUBISHI CHEMICAL

www.resindion.com

ReliZyme[™]

ReliZyme™ products line

	ReliZyme ™	Functional group	Application technologies examples
READY TO USE for multipoint covalent binding	EP	°~4	Resindion acquired a big experience in beta-lactams intermediate production in
	HFA		pharma industries, in particular:7-ADCA production
	SHY	n = short arm	7-ACA production6-APA production.
	LHY	n = long arm	Many other existing and potential applications, also in the food and pharma market
Multipoint covalent and ionic binding	EA	M [™] [™]	areas: ✓ Amino acylase – lyase
	НА	MH ₆ NH ₂	✓ Beta-amylase✓ Cellulases
	QA	N Car	 ✓ Cyclodextrineglucano transferase
	IDA		✓ Gluco-amylase✓ Glucoisomerase
Physical adsorption	HG	ОН	✓ Hydantoinase✓ Lipases
	BU		✓ Nitrilases✓ Nitril hydratase
	RB1	RB1	✓ Peroxidase✓ Pullulanase
	RB3	RB3	✓ Trypsin

Handling and storage

ReliZyme™ are delivered in wet form.

Users are requested to observe the generally accepted precautions for the handling of chemicals and to follow the health and safety recommendations set out in each ReliZymeTM SDS. ReliZymeTM ready to use types have to be stored at 4 - 6 °C and for no longer than 3-6 months in the original sealed packing. All the other products can be stored at room temperature in the original sealed packing.

Resindion S.r.l.

A Group Company of 📩 MITSUBISHI CHEMICAL

Typical features

ReliZyme™ are Resindion products designed for biocatalytic applications and they are characterized by rigid methacrylic polymer matrix and very high physical and chemical stability.


Special ReliZyme™ products can be designed on purpose according to customer's needs:

- different ligands
- different porosity
- different particle size distribution.

	Particle size range (µm)	
	S grade	M grade
ReliZyme™ 112		
ReliZyme™ 113]	
ReliZyme™ 403	100 - 300	200 – 500
ReliZyme™ RB1		
ReliZyme™ RB3	1	




EP and HFA resins → Multipoint covalent binding



Pressure drop in water at 25 °C

Amino resins → Multipoint covalent binding via preactivation



The outstanding mechanical stability of ReliZymeTM products compared to a competitor resin having the same particle size is shown below;



columns and

(peq)

M grade

This feature makes **ReliZyme™** suitable for the use in both columns and stirring biocatalysis reactors.

www.resindion.com

10



ReliZyme[™]

Material Support File



- Resindion S.R.L., an UNI EN ISO 9001:2015 certified Company, offers the following regulatory documents for each product
- technical data sheet and relevant technical literature
- certificate of analysis
- SISTEMA DI GESTIONE QUALITÀ CERTIFICATO • safety data sheet.

All substances used in the manufacture of ReliZyme™ are selected among those reported in the European Resolution ResAP (2004) 3 Version 3 – 28.01.2009, which is related to the resins that can be used in the processing of foodstuffs.

Customer service

Resindion S.R.L. qualified technical and marketing team grants all the necessary customer assistance, from ReliZyme™ selection to a periodical analytical control of the products characteristics during operation. Please contact Resindion at: customerservice@resindion.com or technicalservice@resindion.com .

Resindion Product Lines





a sustainable condition which is confortable for people, society and the Earth, trascending time and generations.

Sustainability and the betterment of life, through the use of Good Chemistry For Tomorrow, are at the core of everything we are doing.

Resindion S.r.l.

A Group Company of AMITSUBISHI CHEMICAL

Resindion S.r.l.

Via Roma 55			
20082 Binasco (MI), Italy			
Phone:	+39 02 9001301		
Fax:	+39 02 90047687		
E-mail:	info@resindion.com		
Web site:	www.resindion.com		

Mitsubishi Chemical Corporation

 10F Gate City Ohsaki East Tower

 1-11-2, Osaki, Shinagawa-ku

 Tokyo 141-0032, Japan

 Phone:
 +81 3 6748 7146

 Fax:
 +81 3 5487 6810

 Web site:
 www.diaion.com



© 2018 Resindion S.r.l. - All rights reserved

Neither this publication, nor any product in this brochure shall be construed as recommending the infringement of any patent, nor extending any license, expressed or implied, nor assuming any liability under any issued or pending patent. The data presented have been carefully compiled from Resindion records which are believed to be accurate and reliable. However, no warranties or representations with respect hereto are made, nor is freedom from any patent to be inferred.